

Structured Electronic Design

Two-step design of negative feedback amplifiers

Anton J.M. Montagne

Two-step design method

Two-step design method

Feedback amplifier comprises:

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Fixes ideal value(s) of the amplifier's transmission-1 matrix parameter(s)

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Fixes ideal value(s) of the amplifier's transmission-1 matrix parameter(s)

Controller(s)

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Fixes ideal value(s) of the amplifier's transmission-1 matrix parameter(s)

Controller(s)

Minimizes error between ideal and actual value of the amplifier's transmission-1 matrix parameter(s)

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Fixes ideal value(s) of the amplifier's transmission-1 matrix parameter(s)

Controller(s)

Minimizes error between ideal and actual value of the amplifier's transmission-1 matrix parameter(s)

Two-step design:

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Fixes ideal value(s) of the amplifier's transmission-1 matrix parameter(s)

Controller(s)

Minimizes error between ideal and actual value of the amplifier's transmission-1 matrix parameter(s)

Two-step design:

1. Design of feedback network(s) using nullors as controller(s)

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Fixes ideal value(s) of the amplifier's transmission-1 matrix parameter(s)

Controller(s)

Minimizes error between ideal and actual value of the amplifier's transmission-1 matrix parameter(s)

Two-step design:

1. Design of feedback network(s) using nullors as controller(s)
2. Design of controller(s)

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Fixes ideal value(s) of the amplifier's transmission-1 matrix parameter(s)

Controller(s)

Minimizes error between ideal and actual value of the amplifier's transmission-1 matrix parameter(s)

Two-step design:

1. Design of feedback network(s) using nullors as controller(s)
2. Design of controller(s)

Budgets for processing errors should be split:

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Fixes ideal value(s) of the amplifier's transmission-1 matrix parameter(s)

Controller(s)

Minimizes error between ideal and actual value of the amplifier's transmission-1 matrix parameter(s)

Two-step design:

1. Design of feedback network(s) using nullors as controller(s)
2. Design of controller(s)

Budgets for processing errors should be split:

Contributions of feedback network(s)

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Fixes ideal value(s) of the amplifier's transmission-1 matrix parameter(s)

Controller(s)

Minimizes error between ideal and actual value of the amplifier's transmission-1 matrix parameter(s)

Two-step design:

1. Design of feedback network(s) using nullors as controller(s)
2. Design of controller(s)

Budgets for processing errors should be split:

Contributions of feedback network(s)

Contributions of controller

Two-step design method

Feedback amplifier comprises:

Feedback network(s)

Fixes ideal value(s) of the amplifier's transmission-1 matrix parameter(s)

Controller(s)

Minimizes error between ideal and actual value of the amplifier's transmission-1 matrix parameter(s)

Two-step design:

1. Design of feedback network(s) using nullors as controller(s)
2. Design of controller(s)

Budgets for processing errors should be split:

Contributions of feedback network(s)

Contributions of controller

Performance limitations affected by the feedback network

Performance limitations affected by the feedback network

Noise performance of the amplifier

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Power efficiency of the amplifier

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Power efficiency of the amplifier

Passive feedback networks enlarge power losses of the controller

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Power efficiency of the amplifier

Passive feedback networks enlarge power losses of the controller

Dissipative feedback networks dissipate power themselves

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Power efficiency of the amplifier

Passive feedback networks enlarge power losses of the controller

Dissipative feedback networks dissipate power themselves

Frequency response

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Power efficiency of the amplifier

Passive feedback networks enlarge power losses of the controller

Dissipative feedback networks dissipate power themselves

Frequency response

poles / zeros in transfer of feedback network become
zero / poles in the amplifier's transfer

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Power efficiency of the amplifier

Passive feedback networks enlarge power losses of the controller

Dissipative feedback networks dissipate power themselves

Frequency response

poles / zeros in transfer of feedback network become
zero / poles in the amplifier's transfer

Nonlinearity

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Power efficiency of the amplifier

Passive feedback networks enlarge power losses of the controller

Dissipative feedback networks dissipate power themselves

Frequency response

poles / zeros in transfer of feedback network become
zero / poles in the amplifier's transfer

Nonlinearity

nonlinear in transfer of feedback network becomes
inverse nonlinear transfer of the amplifier

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Power efficiency of the amplifier

Passive feedback networks enlarge power losses of the controller

Dissipative feedback networks dissipate power themselves

Frequency response

poles / zeros in transfer of feedback network become zero / poles in the amplifier's transfer

Nonlinearity

nonlinear in transfer of feedback network becomes inverse nonlinear transfer of the amplifier

Temperature stability and ageing

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Power efficiency of the amplifier

Passive feedback networks enlarge power losses of the controller

Dissipative feedback networks dissipate power themselves

Frequency response

poles / zeros in transfer of feedback network become zero / poles in the amplifier's transfer

Nonlinearity

nonlinear in transfer of feedback network becomes inverse nonlinear transfer of the amplifier

Temperature stability and ageing

Changes in transfer feedback networks results in changes of the amplifier's transfer

Performance limitations affected by the feedback network

Noise performance of the amplifier

Passive feedback networks enlarge contribution of controller noise to total amplifier noise

Dissipative feedback networks contribute to amplifier noise

Power efficiency of the amplifier

Passive feedback networks enlarge power losses of the controller

Dissipative feedback networks dissipate power themselves

Frequency response

poles / zeros in transfer of feedback network become zero / poles in the amplifier's transfer

Nonlinearity

nonlinear in transfer of feedback network becomes inverse nonlinear transfer of the amplifier

Temperature stability and ageing

Changes in transfer feedback networks results in changes of the amplifier's transfer

Contribution controller performance limitations to those of amplifier

Contribution controller performance limitations to those of amplifier



In which way, and to what extent do performance limitations of the controller contribute to performance limitations of the amplifier?

Contribution controller performance limitations to those of amplifier



In which way, and to what extent do performance limitations of the controller contribute to performance limitations of the amplifier?



To study this we need an appropriate feedback model!

Contribution controller performance limitations to those of amplifier

?

In which way, and to what extent do performance limitations of the controller contribute to performance limitations of the amplifier?

!

To study this we need an appropriate feedback model!

This model should describe the transfer as the product of the ideal transfer (controller(s) == nullors) and a function that shows the influence of the controller performance limitations.

Contribution controller performance limitations to those of amplifier

?

In which way, and to what extent do performance limitations of the controller contribute to performance limitations of the amplifier?

!

To study this we need an appropriate feedback model!

This model should describe the transfer as the product of the ideal transfer (controller(s) == nullors) and a function that shows the influence of the controller performance limitations.

Type of limitations that should be covered by the model

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift
Bandwidth limitations

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift

Bandwidth limitations

Weak nonlinearity

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift
Bandwidth limitations
Weak nonlinearity



Error-reduction capabilities
of negative feedback

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift
Bandwidth limitations
Weak nonlinearity



Error-reduction capabilities
of negative feedback

No

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift
Bandwidth limitations
Weak nonlinearity



Error-reduction capabilities
of negative feedback

No

Noise contribution of controller

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift
Bandwidth limitations
Weak nonlinearity



Error-reduction capabilities
of negative feedback

No

Noise contribution of controller
V/I drive capability of controller (clipping)

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift
Bandwidth limitations
Weak nonlinearity



Error-reduction capabilities
of negative feedback

No

Noise contribution of controller
V/I drive capability of controller (clipping)
Biasing and offset errors of controller

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift
Bandwidth limitations
Weak nonlinearity



Error-reduction capabilities
of negative feedback

No

Noise contribution of controller
V/I drive capability of controller (clipping)
Biasing and offset errors of controller

?

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift
Bandwidth limitations
Weak nonlinearity



Error-reduction capabilities
of negative feedback

No

Noise contribution of controller
V/I drive capability of controller (clipping)
Biasing and offset errors of controller

?

Influence of parasitic impedances between
controller terminal and ground

Type of limitations that should be covered by the model

Controller performance limitations that are reduced by feedback:

Yes

Gain inaccuracy / drift
Bandwidth limitations
Weak nonlinearity



Error-reduction capabilities
of negative feedback

No

Noise contribution of controller
V/I drive capability of controller (clipping)
Biasing and offset errors of controller

?

Influence of parasitic impedances between
controller terminal and ground