Structured Electronic Design

Phantom Zero Compensation Interaction with other Design Aspects

Anton J.M. Montagne

Interaction with other performance aspects and cost factors, such as: - Noise performance

- Noise performance
- Accuracy

- Noise performance
- Accuracy
- Linearity

- Noise performance
- Accuracy
- Linearity
- Power losses

- Noise performance
- Accuracy
- Linearity
- Power losses
- Energy storage

Interaction with other performance aspects and cost factors, such as:

- Noise performance
- Accuracy
- Linearity
- Power losses
- Energy storage

Low if:

Interaction with other performance aspects and cost factors, such as:

- Noise performance
- Accuracy
- Linearity
- Power losses
- Energy storage

Low if:

The impedances inserted in series or in parallel with the signal path can be ignored in the frequency range of interest.

Interaction with other performance aspects and cost factors, such as:

- Noise performance
- Accuracy
- Linearity
- Power losses
- Energy storage

Low if:

The impedances inserted in series or in parallel with the signal path can be ignored in the frequency range of interest.

This is always the case for impedances that establish a phantom zero for frequency compensation because such zeros are located at the edges of the frequency band of interest.

Interaction with other performance aspects and cost factors, such as:

- Noise performance
- Accuracy
- Linearity
- Power losses
- Energy storage

Low if:

The impedances inserted in series or in parallel with the signal path can be ignored in the frequency range of interest.

This is always the case for impedances that establish a phantom zero for frequency compensation because such zeros are located at the edges of the frequency band of interest.

Increase of out-of band loop gain beneficial to out-of-band linearity

Interaction with other performance aspects and cost factors, such as:

- Noise performance
- Accuracy
- Linearity
- Power losses
- Energy storage

Low if:

The impedances inserted in series or in parallel with the signal path can be ignored in the frequency range of interest.

This is always the case for impedances that establish a phantom zero for frequency compensation because such zeros are located at the edges of the frequency band of interest.

Increase of out-of band loop gain beneficial to out-of-band linearity